


Permanent magnets



Product	
M	Magnet
MC	Magnet, Customer-specific
MA	Magnet, Customer-specific acc. AS9100
MT	Magnet, Customer-specific acc. IATF16949
MZ	Special magnet (when one of characters below = 'Z')

Shape			
A	Axle (L > 1,5 x D)	G	Globe/Sphere
B	Block (Rectangle)	H	Horseshoe
D	Disk	P	Point
F	Foil	R	Ring
S	Segment (part of a disc or ring)	T	Trapezium/Triangle
Z	Special		

Magnet material <small>... For magnet material explanation: see page 2</small>			
A ...	Aluminium-nickel-cobalt (AlNiCo)	N ...	Neodymium (NdFeB)
B	Aluminium-nickel-cobalt (AlNiCo) Polymer	P...	Neodymium (NdFeB) Polymer
F ...	Ferrite (SrFe)	Q ...	Neodymium (NdFeB) Stabilized
G	Ferrite (SrFe) Polymer	I	Iron-containing material
S ...	Samarium-Cobalt (SmCo)	Z	Special
T	Samarium-Cobalt (SmCo) Polymer	... Z	Special (in case of A/F/N/P/Q/S)

Magnetization direction + pole pairs <small>... For magnetization explanation: see page 3</small>			
A...	Axial (single or alternating poles)	J...	Segment radial
B...	Through the height	K...	Segment diametric
D...	Radial	L...	Lateral (in lines on surface)
E...	Diametric	Z...	Special (e.g. horseshoe)
G...	Multi-poled on outer contour	...N	NOT magnetized
H...	Multi-poled on inner contour	...x	x = Number of pole pairs (9 = max. multipole)
I...	One-sided multi-poled		

Size [mm]			
L = Length, W = Width, H = Height, D = Diameter, R = Radius, T = Thickness, A = Angle [°]			
See examples. No 'leading zeros'. Separator is point (not comma).			
Notation:	Shape:	Example:	Remark:
L x W x H*	Block	123x12x12.3	H* = magn. direction - LxW in decreasing order
DD x H	Disk	D123.4x123	
W x T x L	Foil	1234x1.0x12345	always min. 1 decimal in thickness
DD	Globe	D123.4	
H x W x T x Y	Horseshoe	123x123x12x123	Y=distance between legs - see page 4 for drawing
L x W x H <A	Point	123x12x12<123	
DD x dd x H	Ring	D1234xd123x123	
RR x rr x H <A	Segment	R12xr12x12<123	
L x W/W x H	Trapezium	123x21/12x12	
L x W x H	Triangle	123x12x12	
L x L x L	Special shape	1234x123x123	dimensions in decreasing order

Coating (for all shapes except foil)			
B	Basic (no coating)	PA	Passivated
CI	Zinc	PL	Parylene
CB	Zinc blue	NI	Ni
CY	Yellow zinc Cr3+	NC	NiCu
EP	Epoxy	NX	NiCu epoxy
		NY	NiCuNi epoxy
		NN	NiCuNi
		NS	NiCuNi shiny
		NA	NiCuNi+Au
		NU	NiCuSn
		TN	Tin
		Z	Special coating

Colour/adhesive type (for foil only):
[see page 4](#)

Permanent magnets

Magnet material

A ... : Aluminium-nickel-cobalt (AlNiCo)			
Cast:		Sintered:	
A5A	GSA-5A	AS5	GSAS-5
A5B	GSA-5B	AS6	GSAS-6
A6	GSA-6	AS8	GSAS-8
A7	GSA-7		
A8A	GSA-8A		
A8B	GSA-8B		
A9A	GSA-9A		
A9B	GSA-9B		

F ... Ferrite (SrFe)	
F10	GSF-10 (isotropic)
F25	GSF-25 (anisotropic)
F30	GSF-30 (anisotropic)
F33	GSF-33 (anisotropic)
F34	GSF-34 (anisotropic)
F40	GSF-40 (anisotropic)
F42	GSF-42 (anisotropic)
F44	GSF-44 (anisotropic)
F45	GSF-45 (anisotropic)
F47	GSF-47 (anisotropic)
Flexible (foil):	
FN04	Quality NF04 (isotropic) [Std]
FN06	Quality NF06 (isotropic)
FN07	Quality NF07 (semi-anisotropic)
FN11	Quality NF11 (anisotropic) [Std]

S ... : Samarium-Cobalt (SmCo)	
S20	GSS-20
S22	GSS-22
S24	GSS-24
S26	GSS-26
S28	GSS-28
S30	GSS-30
S32	GSS-32

N ... : Neodymium (NdFeB)	
N35	GSN-35
N38	GSN-38
N40	GSN-40
N42	GSN-42
N45	GSN-45
N48	GSN-48
N50	GSN-50
N52	GSN-52
N54	GSN-54

N33M	GSN-33M
N35M	GSN-35M
N38M	GSN-38M
N40M	GSN-40M
N42M	GSN-42M
N45M	GSN-45M
N48M	GSN-48M
N50M	GSN-50M
N52M	GSN-52M
N30H	GSN-30H
N33H	GSN-33H
N35H	GSN-35H
N38H	GSN-38H
N40H	GSN-40H
N42H	GSN-42H
N44H	GSN-44H
N46H	GSN-46H
N48H	GSN-48H
N50H	GSN-50H
N52H	GSN-52H
N30SH	GSN-30SH
N33SH	GSN-33SH
N35SH	GSN-35SH
N38SH	GSN-38SH
N40SH	GSN-40SH
N42SH	GSN-42SH
N44SH	GSN-44SH
N46SH	GSN-46SH
N48SH	GSN-48SH
N50SH	GSN-50SH
N52SH	GSN-52SH
N28UH	GSN-28UH
N30UH	GSN-30UH
N33UH	GSN-33UH
N35UH	GSN-35UH
N38UH	GSN-38UH
N40UH	GSN-40UH
N42UH	GSN-42UH
N45UH	GSN-45UH
N48UH	GSN-48UH
N50UH	GSN-50UH
N28EH	GSN-28EH
N30EH	GSN-30EH
N33EH	GSN-33EH
N35EH	GSN-35EH
N38EH	GSN-38EH
N40EH	GSN-40EH
N42EH	GSN-42EH
N45EH	GSN-45EH

N28AH	GSN-28AH
N30AH	GSN-30AH
N33AH	GSN-33AH
N35AH	GSN-35AH
N38AH	GSN-38AH
N40AH	GSN-40AH
N42AH	GSN-42AH
N25BH	GSN-25BH
N28VH	GSN-28VH
N30VH	GSN-30VH
N33VH	GSN-33VH
N35VH	GSN-35VH
N38VH	GSN-38VH

Flexible (foil):	
NR2	Quality R2 (isotropic)
NR3	Quality R3 (isotropic)
NR4	Quality R4 (isotropic)
NR5	Quality R5 (isotropic)
NR6	Quality R6 (isotropic)
NR7	Quality R7 (isotropic)
NR8	Quality R8 (isotropic)
NR9	Quality R9 (isotropic)
NRE2	Quality RE2 (isotropic)
NRE3	Quality RE3 (isotropic)
NRE4	Quality RE4 (isotropic)
NRE5	Quality RE5 (isotropic)
NRE6	Quality RE6 (isotropic)

P ... : Neodymium (NdFeB) Polymer			
Compression:		Injection:	
6C	GSNB-6C	3I	GSNB-3I
8AC	GSNB-8AC	4I	GSNB-4I
8C	GSNB-8C	5I	GSNB-5I
8BC	GSNB-8BC	5AI	GSNB-5AI
8CC	GSNB-8CC	6I	GSNB-6I
9C	GSNB-9C	6AI	GSNB-6AI
10C	GSNB-10C	7I	GSNB-7I
11C	GSNB-11C		
11AC	GSNB-11AC		
12AC	GSNB-12AC		

Q ... : Neodymium (NdFeB) Stabilized	
Q53N	GSNS53N
Q50M	GSNS50M
Q35EH	GSNS35EH
Q30AH	GSNS30AH
Q33AH	GSNS33AH

Permanent magnets

Magnetization direction					
Code	Description	Schematic	Isotropic	Anisotropic	Examples
A...	Axial (single / alternating poles)	<p>One pole pair Alternating pole pairs</p>	I	A	One pole pair: Speakers, holding devices, magnetic switches, insert gas switches Alternating poles: Synchronous motors, disc coupling
B...	Through the height (thickness)		I	A	Filtering systems Clamping devices Magnetic chokes Switches
D...	Radial		I		Holding magnets Couplings (limited sizes available)
E...	Diametric		I		Synchronous motors
G...	Multi-poled on outer contour		I		Dynamos Motors Concentric ring Couplings
H...	Multi-poled on inner contour		I		Motors Concentric ring Couplings
I...	One-sided multi-poled		I		Memo magnets & flexible
J...	Segment radial		I	A	Motors
K...	Segment diametric		I	A	Motors
L...	Lateral (in lines on surface)		I		Holding devices Magnetic chokes

Permanent magnets

Colour/adhesive type (for foil only)

BN	Brown - base material
BL	Blue
BK	Black
GN	Green
GY	Grey
OR	Orange
RD	Red
WT	White
YL	Yellow
AB	Adhesive Basic
AF	Adhesive Foam
AS	Adhesive Strong
Z	Special colour/combination

Dimension overview horseshoe magnet:

